



**IDEAL FOR**

- REO CONCRETE**  
 ●●●●○
- MASONRY**  
 ●●●●●
- BRICKS**  
 ●●●●●
- CONCRETE BLOCK**  
 ●●●●●

**HANG TAG**  
Supplied on hang tag



**ZENTRO®**

# SDS Plus 4 Head Cut

**4 HEAD CUT**

Dynamic drilling ability, with secondary cutters protecting the drill bit in the event of reinforcement collision

**SUITS**

SDS ROTARY HAMMER DRILL



Masonry References | **PG 175**



Click or Scan & See |



Click or Scan | **Pack Sizes**



METRIC			HANG TAG
ø mm	OAL mm	WL mm	CODE   1 PCE
5.0	110	50	SPZ050110
	160	100	SPZ050160
5.5	110	50	SPZ055110
	160	100	SPZ055160
6.0	110	50	SPZ060110
	160	100	SPZ060160
6.5	110	50	SPZ065110
	160	100	SPZ065160
8.0	110	50	SPZ080110
	160	100	SPZ080160
10.0	110	50	SPZ100110
	160	100	SPZ100160
12.0	160	100	SPZ120160
	210	150	SPZ120210
13.0	260	200	SPZ130260
	310	250	SPZ130310
14.0	260	200	SPZ140260
	450	400	SPZ140450
15.0	1000	950	SPZ1401000
	210	150	SPZ150210
16.0	160	100	SPZ160160
	260	200	SPZ160260
18.0	450	400	SPZ160450
	250	200	SPZ180250
20.0	450	400	SPZ180450
	250	200	SPZ200250
22.0	450	400	SPZ200450
	250	200	SPZ220250
24.0	450	400	SPZ220450
	250	200	SPZ240250
25.0	450	400	SPZ240450
	250	200	SPZ250250
28.0	450	400	SPZ250450
	250	200	SPZ280250
30.0	450	400	SPZ280450
	250	200	SPZ300250
32.0	450	400	SPZ300450
			SPZ320450

IMPERIAL			HANG TAG
ø mm	OAL mm	WL mm	CODE   1 PCE
3/8"	160	110	SPZ138X160*



4 x 90° geometry with four specifically developed cutting edges of equal height for precise, accurate holes for professional fixings.



Radially shaped edges for protection when hitting rebar, preventing jamming and increasing operational life.



Robust, one-piece carbide tip perforates rebar with permanent strength and constant precision.



**Wear markers** indicate if the drill bit is still suited for drilling holes for plug and anchor fixtures.