

PVC POWER CABLES



AUSTRALIA PACIFIC ELECTRIC CABLES

PVC Insulated, PVC Sheathed,
Three core plus insulated earth flat,
1.5mm² 450/750V to AS/NZS 5000.2

Conductor: Plain annealed copper.

Insulation: PVC V90


Sheath: PVC 3V90

compounds for continuous conductor temperature of 90°C.

Standard Colours

Cores: Black, Red
Green/Yellow (earth), White

Sheath: Blue
100 mtr Packs only



Power Conductor		Earth Conductor		Average Sheath thickness mm	Approx overall dimensions mm	Approx. mass kg/100m	Product Code
Nominal conductor area mm ²	Average insulation thickness mm	Nominal conductor area mm	Average insulation thickness mm				
1.5	0.6	1.5	0.6	0.9	12.7 x 4.6	12.6	BAC4705

Brisbane Office and Factory

89 Platinum Street,
Crestmead, Qld 4132
P: 07 3802 3651
E: bnsales@apeccables.com.au

Melbourne Sales & Distribution

188 Holt Parade,
Thomastown, VIC 3074
P: 03 9465 1188
E: salesmdc@apeccables.com.au

Perth Sales & Distribution

638 Casella Place
Kewdale, WA 6105
P: 08 9350 1300
E: salespdc@apeccables.com.au