



Perfect for.....
Deep hole drilling in a wide range
of diameters

- A Back Tapered Flute**
Precision ground back tapered flute prevents drill from jamming in holes and provides easy tool removal
- B Thin Core**
Thin body core with deep flutes allows greater removal of wood chips
- C 'In Flute' Steam Tempering**
The 'In Flute' is steam tempered to provide a smooth finish which allows rapid removal of wood chips and faster drilling
- D Precision Machined 'Spur'**
Precision machined 'spur' scores the outline of the hole into the wood, helping the bit to stay true and produce clean holes with minimal break through
- E Screw Tip**
Screw tip pulls the auger through the wood for added ease of use and minimal user effort

- Wood Augers can be used in:**
- Hardwoods
 - Softwoods
 - Veneered chipboard
 - Plywood
 - Chipboard
- Wood Augers are ideal when:**
- Producing holes in timber from 6-32mm
 - Cable or pipe passage through joists

Our wood augers are available on either a Hex or SDS Plus shank to fit your machine requirements



DID YOU KNOW?

Wood Augers are one of the oldest drill bit designs still in manufacture today and were originally produced with shank designs to fit into manually operated drilling braces

TECH TIP!

Our Wood Augers are available in a variety of lengths ranging from 100mm to 450mm

Wood Auger Drill Bits - SDS Plus shank

Diameter Size mm	Overall Length mm	Working Length mm	Part Number
8	205	125	WS08.0X205
10	205	125	WS10.0X205
12	205	125	WS12.0X205
12	400	360	WS12.0X400
16	205	125	WS16.0X205
16	400	360	WS16.0X400
20	205	125	WS20.0X205
22	205	125	WS22.0X205
22	400	360	WS22.0X400
25	205	125	WS25.0X205



Wood Auger Drill Bits - Hexagon Shank

Diameter Size mm	Overall Length mm	Working Length mm	Part Number
6	235	160	WH06.0X235
8	235	160	WH08.0X235
10	235	160	WH10.0X235
10	450	380	WH10.0X450
12	235	160	WH12.0X235
12	450	380	WH12.0X450
13	235	160	WH13.0X235
16	235	160	WH16.0X235
16	450	380	WH16.0X450
18	235	160	WH18.0X235
20	100	65	WH20.0X100
20	235	160	WH20.0X235
20	450	380	WH20.0X450
22	235	160	WH22.0X235
22	450	380	WH22.0X450
25	155	110	WH25.0X155
25	235	160	WH25.0X235
25	450	380	WH25.0X450
32	155	110	WH32.0X155
32	235	160	WH32.0X235



Operation Speed Chart

Diameter Size mm	Softwood RPM	Hardwood RPM
6 - 10	2000	1500
11 - 15	1500	1250
16 - 20	1250	1000
21 - 25	1000	750
26 - 32	750	50

*Please visit www.armeg.co.uk for full operation speed chart

