



Perfect for.....
The smoothest and fastest wood drill bits available



- A

1/4" Quick-Change shank* for added convenience and rapid diameter tool change. Impact rated for impact drivers.
- B

Short lightweight body construction for maximum holes per charge in cordless machines
- C

Four deep auger style flutes for rapid chip evacuation and faster drilling speeds
- D

Four precision ground cutting teeth for extreme drilling comfort and balance
- E

Purpose designed head geometry for ultra clean breakthrough

*Apart from 32mm which has a 7/16" shank & can't be used in impact drivers.



STUBBY LENGTH

Ideal for Joists

The 120mm Stubby WoodBeaver is Ideal for:

- Inter-joist drilling
- Working in tight spaces
- Users with larger drilling machines

DID YOU KNOW?

All WoodBeaver designs are precisely back-tapered along the length of the flute. The design is invisible to the naked eye, but creates a jam-free, smooth action when removing drill bits from holes drilled in wood



WoodBeaver can be used in:

- Hardwoods
- Softwoods
- Veneered chipboard
- Plywood
- Chipboard

WoodBeaver is ideal for:

- Producing cable / pipe passages through timber etc

TECH TIP!

When being used in a cordless drill, the larger WoodBeavers should be used on the slowest speed. The slowest speed gives the higher torque required. Using on higher speeds only provides a low torque which could stall the machine out

WoodBeaver

Diameter Size mm	Overall Length mm	Working Length mm	Part Number
10	165	125	WWB10.0T
12	165	125	WWB12.0T
13	165	125	WWB13.0T
16	165	125	WWB16.0T
18	165	125	WWB18.0T
19	165	125	WWB19.0T
20	165	125	WWB20.0T
22	165	125	WWB22.0T
25	165	125	WWB25.0T
32	165	125	WWB32.0T
4 Piece WoodBeaver Set	1 X 16 / 20 / 25 / 32mm		WWB4PCSET

Stubby WoodBeaver

Diameter Size mm	Overall Length mm	Working Length mm	Part Number
16	120	80	WWBST16
20	120	80	WWBST20
22	120	80	WWBST22
25	120	80	WWBST25
32	120	80	WWBST32
3 Piece Stubby WoodBeaver Set	1 X 16 / 20 / 25mm 1 X Quick-Change SDS Plus to 1/4" Adaptor		WWB3PCSET120

WoodBeaver Accessories

	Drive Type	Length mm	Internal mm	Technical Product Detail	Part Number
Quick-Change SDS Plus to 1/4" Adaptor *Twister Impact rated for impact drivers	SDS Plus	60	1/4"	For Sizes 10 - 25mm	SDS1/4WB055
7/16" SDS Plus drive adaptor	SDS Plus	90	7/16"	For Sizes 32mm only	SDS7/16WB090
Quick-Change 1/4" Extension Rod *Twister Impact rated for impact drivers	1/4" Hexagon	230	1/4"	For Sizes 10 - 25mm	WWB1/4HEX250

Scan me for demo video





32mm Wood Beavers have min. chuck requirement of 13mm



1/4" shank (except 32mm WoodBeavers)



7/16" shank (32mm WoodBeaver only)



When used with relevant adaptor



M6x6 (7/16" adaptor grub screws)



3mm (7/16" adaptor grub screws)



Up to 25mm only