

Luminaires | Anti Corrosives

**LinearPacCWS™ Colour  
and Wattage Switchable  
1200mm Anti-Corrosive**

AU-ANT1200CWS



Photometrics

<b>Wattage</b>	14 / 18 / 24 / 28
<b>Lumens</b>	2520 - 5050
<b>Lm/W</b>	180
<b>Lumens in EM Mode</b>	250lm
<b>Beam Angle</b>	120
<b>Colour Temperature</b>	3000 / 4000 / 6500
<b>RA</b>	80
<b>SDCM</b>	6
<b>UGR</b>	>28

Product Features

<b>Brand</b>	Aurora
<b>IP Rating</b>	IP66
<b>IK Rating</b>	IK10
<b>L70 Hours</b>	50,000
<b>Lifetime Class</b>	L80 B10
<b>SKU Type</b>	Non Dim
<b>Dimmable</b>	No

<b>Warranty</b>	5 Years
<b>Onsite Warranty</b>	3 Years
<b>EEL Class</b>	N/A
<b>Country of origin</b>	CN

### Electrical Specification

<b>Input Voltage (Min)</b>	220
<b>Input Voltage (Max)</b>	240
<b>Input Voltage Type</b>	AC
<b>Power Factor</b>	0.9
<b>Surge Protection (kV)</b>	2.0
<b>Inrush Current (A)</b>	10
<b>Protection class</b>	Class 1
<b>Frequency (Min) Hz.</b>	50HZ
<b>Frequency (Max) Hz.</b>	60HZ
<b>Operating Temp. (Min) °C</b>	-20
<b>Operating Temp. (Max) °C</b>	40

### Physical Attributes

<b>Length (mm)</b>	1270
<b>Width (mm)</b>	96
<b>Height (mm)</b>	78
<b>Material</b>	Polycarbonate
<b>Optic Material</b>	Opal Polycarbonate
<b>RAL Colour code</b>	N/A
<b>Finish Colour</b>	Grey

### Features

<b>Marketing Feature 1</b>	Colour switchable between 3000K/4000K/6500K
<b>Marketing Feature 2</b>	Wattage switchable for 2ft, 4ft, 5ft, 6ft variants
<b>Marketing Feature 3</b>	Delivers up to 180lm/W
<b>Marketing Feature 4</b>	Plug and play Emergency, Emergency Self Test and Microwave Sensor with Corridor function

<b>Marketing Feature 5</b>	Pre-drilled cable entry points on the back and ends, suitable for 20mm conduit
<b>Marketing Feature 6</b>	Wide surface bracket rail for flexibility whilst mounting
<b>Marketing Feature 7</b>	Detachable 4 way loop in/loop out terminal block which can be positioned in 4 locations
<b>Marketing Feature 8</b>	BESA mounting points on the back
<b>Marketing Feature 9</b>	304 stainless steel fixing clips which can be fixed in the open position
<b>Marketing Feature 10</b>	DALI converter pack available
<b>Marketing Feature 11</b>	IP66 rated
<b>Marketing Feature 12</b>	IK10 rated
<b>Marketing Feature 13</b>	L70 50,000h
<b>Marketing Feature 14</b>	5 year warranty
<b>Marketing Feature 15</b>	3 year on-site warranty (registration required) *Terms and conditions apply