Datasheet
SKU: AU-DDL10160CS

Luminaires | Downlights

SpryteCS™ Colour Switchable Fixed Polycarbonate Downlights

AU-DDL10160CS



Photometrics

Wattage	6
Lumens	550 - 630
Lm/W	105
Beam Angle	60
Colour Temperature	3000 / 4000 / 6500
Ra	650
SDCM	<6
UGR19	NO

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK02
L70 Hours	L70 40,000
Lifetime Class	B50
Dimmable	YES
Warranty	5 Years
Country of Origin	CN

Datasheet

SKU: AU-DDL10160CS

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.7
Surge Protection (kV)	1.5
Protection Class	CLASS TWO
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	NO

Physical Attributes

Height (mm)	53
Overall Diameter (mm)	78
Lamp Base	LED
Cutout Diameter Max. (mm)	60
Material	Polycarbonate
Optic Material	Polycarbonate

Apex Park | 6 Little Burrow | Welwyn Garden City AL7 4SW | United Kingdom | Tel: +44 (0) 1707 228 700

This document is uncontrolled if printed, all information is subject to change. Generated on 30/12/24