

Luminaires | Downlights

SpryteCS™ Colour Switchable Adjustable Polycarbonate Downlights

AU-DDL10260CS



Photometrics

Wattage	6
Lumens	550 - 630
Lm/W	105
Beam Angle	60
Colour Temperature	3000 / 4000 / 6500
RA	80
SDCM	<6

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK02
L70 Hours	L70 40,000
Lifetime Class	B50
Dimmable	YES
0-10V Dimming?	NO
DALI Dimming?	NO
1-10V Dimming?	NO

DALI-2 Dimming?	NO
Warranty	5 Years
Country of origin	CN

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.7
Surge Protection (kV)	1500V
Protection class	CLASS2
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40

Physical Attributes

Height (mm)	54
Overall Diameter (mm)	90
Cutout Diameter Min. (mm)	70
Cutout Diameter Max. (mm)	70
Material	Polycarbonate
Optic Material	Polycarbonate
Diffuser	Clear