Datasheet
SKU: AU-DL15CS

Luminaires | Downlights

Uni-FitCS™ Colour Switchable 15W Fixed Polycarbonate Downlights

AU-DL15CS



General Information

Lumens	1600 - 1700
SKU Description	Uni-Fit™CS 15W Colour Switchable IP44 Non-Dimmable Downlight
Wattage	15
Web Product Description	Uni-FitCS™ Colour Switchable 15W Fixed Polycarbonate Downlights
Lm/W	113
Web Extended Description	Performance and Value - that's what the Uni-FitCS™ range of commercial downlights stands for. Featuring ThermoTec™ technology, integrated driver and high quality LED chips to deliver an outstanding lumen performance. The triac dimmable Uni-FitCS™ range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.
Colour Temperature	3000 / 4000 / 6500
Brand	Aurora
Range Name	Uni-FitCS™
SDCM	<10
RA	80

Apex Park | 6 Little Burrow | Welwyn Garden City AL7 4SW | United Kingdom | Tel: +44 (0) 1707 228 700

This document is uncontrolled if printed, all information is subject to change. Generated on 07/10/24

AURORA® LIGHTING

Datasheet

SKU: AU-DL15CS

Beam Angle	100
Finish Colour	White
Marketing Feature 1	Colour switchable between 3000/4000/6500K
RAL Colour code	NO
Input Voltage (Min)	220
Marketing Feature 2	Compact integrated driver for easy installation and shallow ceiling voids
Input Voltage (Max)	240
Marketing Feature 3	IP44 rated
Input Voltage Type	AC
Marketing Feature 4	TP(a) rated
Warranty	5 Years
Marketing Feature 5	3 year warranty
Country of origin	CN
Surge Protection (kV)	1500
Protection class	CLASS 2
Power Factor	0.9
L70 Hours	L70 40,000
Lifetime Class	B50
Max. Nominal Power	<1
SVM	0.4
IP Rating	IP44
IK Rating	IK02
Dimmable	NO
Output Voltage (Max)	240
Max. Case Temperature (°C)	40
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Chip Manufacturer	SANAN
LED Chip Type	2835
No. of LEDs	120
Frequency (Min) Hz.	50HZ

Apex Park | 6 Little Burrow | Welwyn Garden City AL7 4SW | United Kingdom | Tel: +44 (0) 1707 228 700

This document is uncontrolled if printed, all information is subject to change. Generated on 07/10/24

Datasheet

SKU: AU-DL15CS

Shape	60HZ
SKU Type	Non Dim
Frequency (Max) Hz.	-20
Operating Temp. (Min) °F	-15
Operating Temp. (Max) °F	40
Material	Polycarbonate
Optic Material	Polycarbonate
Diffuser	Opal
Height (mm)	60
Overall Diameter (mm)	150
Cutout Diameter Max. (mm)	120