

### Luminaires | Fire Rated Downlights

## R6™ Colour & Wattage Switchable Fixed Black Baffle Fire Rated Downlight

AU-R63BW/CWS



### Photometrics

<b>Wattage</b>	3.5 / 5.5 / 7.5
<b>Lumens</b>	280-660
<b>Beam Angle</b>	60
<b>Colour Temperature</b>	2700 / 3000 / 4000 / 5700
<b>Ra</b>	>90
<b>SDCM</b>	<4

### Product Features

<b>Brand</b>	Aurora
<b>IP Rating</b>	65
<b>L80 Hours</b>	50,000
<b>Lifetime Class</b>	L80 B50
<b>Dimmable</b>	Triac
<b>Country of Origin</b>	CN
<b>Barcode</b>	5056102075724

### Electrical Specification

<b>Input Voltage Type</b>	AC
<b>Power Factor</b>	0.9

<b>Protection Class</b>	2
<b>Frequency (Min) Hz.</b>	50
<b>Frequency (Max) Hz.</b>	60

## Physical Attributes

<b>Height (mm)</b>	75
<b>Overall Diameter (mm)</b>	88
<b>Cutout Diameter Min. (mm)</b>	75
<b>Finish Colour</b>	White

## Features

<b>Marketing Feature 1</b>	Certified for solid timber, I-joist, and metal web joist ceilings
<b>Marketing Feature 2</b>	FastRFix connector with LENNEL terminals for ease of installation
<b>Marketing Feature 3</b>	Easy glide soft springs suitable for double plaster board ceilings
<b>Marketing Feature 4</b>	Low profile design for use in shallow ceilings
<b>Marketing Feature 5</b>	Supplied with white IP65 polycarbonate bezel
<b>Marketing Feature 6</b>	CRI90 for optimized colour rendering
<b>Marketing Feature 7</b>	Energy Rating C
<b>Marketing Feature 8</b>	L80B50 50,000hrs
<b>Marketing Feature 9</b>	5 Year Warranty