

Fittings / Downlights


Firestay Protector Open Back Non-Integrated Downlight - White



The Firestay Protector Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Part B/C/E compliant
- Suitable for 240V lamps (GU10 lamp holder included)
- Loop in/out terminals for speed of installation
- Die-cast aluminium body
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Low voltage lampholder available separately (Code 09906)
- One fitting to fit all standard type lamps. Simply choose a BELL lamp for the application required (See LED Lamps section)

Technical Specification



Product Code	11850
---------------------	-------

Reference

Guarantee	5 Years
EAN	5013588118505
Commodity Code	9405423990
Country of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	240
IP Rating	IP20

Dimensions

Height (mm)	77
Length (mm)	135
Diameter (mm)	85
Downlight Cut Out (mm)	72

Packaging Information

Single Carton Height (mm)	65
Single Carton Width (mm)	107
Single Carton Depth (mm)	92
Single Carton Weight (kg)	0.17
Individual Volume	0.00064
Inner Box Qty	1
Outer Box Qty	50
Outer Box Height (mm)	350
Outer Box Width (mm)	480
Outer Box Depth (mm)	230
Outer Box Weight (kg)	10