

## Fittings / Downlights


### Firestay Protector Open Back Non-Integrated Shower Downlight - Chrome



The Firestay Protector Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Part B/C/E compliant
- Suitable for 240V lamps (GU10 lamp holder included)
- Loop in/out terminals for speed of installation
- Die-cast aluminium body
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Low voltage lampholder available separately (Code 09906)
- One fitting to fit all standard type lamps. Simply choose a BELL lamp for the application required (See LED Lamps section)

## Technical Specification



|                     |       |
|---------------------|-------|
| <b>Product Code</b> | 11868 |
|---------------------|-------|

### Reference

|                          |               |
|--------------------------|---------------|
| <b>Guarantee</b>         | 5 Years       |
| <b>EAN</b>               | 5013588118680 |
| <b>Commodity Code</b>    | 9405423990    |
| <b>Country of Origin</b> | CN            |
| <b>UNSPSC Code</b>       | 39111515      |

## Technical Specification

|           |      |
|-----------|------|
| Volts (V) | 240  |
| IP Rating | IP65 |

## Dimensions

|                        |     |
|------------------------|-----|
| Height (mm)            | 77  |
| Length (mm)            | 135 |
| Diameter (mm)          | 85  |
| Downlight Cut Out (mm) | 72  |

## Packaging Information

|                           |         |
|---------------------------|---------|
| Single Carton Height (mm) | 65      |
| Single Carton Width (mm)  | 107     |
| Single Carton Depth (mm)  | 92      |
| Single Carton Weight (kg) | 0.18    |
| Individual Volume         | 0.00064 |
| Inner Box Qty             | 1       |
| Outer Box Qty             | 50      |
| Outer Box Height (mm)     | 350     |
| Outer Box Width (mm)      | 480     |
| Outer Box Depth (mm)      | 230     |
| Outer Box Weight (kg)     | 10.5    |