



# Technical Data

## Empty Enclosures

### Brief product description:

IP rated accessories designed to protect against water and dust ingress in the most arduous of conditions

### Features:

- IP66 rated when in use
- Provides the ability to self-configure to suit the application
- Suitable for all products in the Nexus Moulded, Grid, Euro Module or Nexus Metal ranges (\*20A Switches and Fused Connection Units with bottom flex outlet not suitable for use)

### Product Images



WP1GEC






WP2GEC





### Technical Specifications

Dimensions (W x H x D) cm	117.5 x 159 x 81 (WP1GEC)
	177.5 x 159 x 81 (WP2GEC)
RoHS Directive	No
WEEE Directive	No
IP Rating	IP66


### Line Diagrams



WP1GEC



WP2GEC



# Empty Enclosures

## Packaging Information

Cat No.	Description	Packaging Type			Pack Quantity			Barcode		
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box
WP1GEC	Single	White Box	n/a	Shipping Carton	1	n/a	10	5050765030090	/	5015056513478
WP2GEC	Double	White Box	n/a	Shipping Carton	1	n/a	10	5050765030106	/	5015056513485

## Weights & Dimensions

Cat No.	Description	Dimension (W x L x H) cm			Weight (kg)			CMB (m <sup>3</sup> )
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Outer Box
WP1GEC	Single	11.6 x 15.5 x 8.2	n/a	48 x 26 x 19	0.35	n/a	5.1	0.024
WP2GEC	Double	17.7 x 15.5 x 8.2	n/a	48.5 x 38.2 x 19.5	0.4	n/a	5.9	0.036

## Installation Information

### Safety Warning

Before use please read carefully and use in accordance with these safety wiring instructions.

Before commencing any electrical work ensure the supply **is switched off at the mains**. Either by switching off the consumer unit or by removing the appropriate fuse.

Wiring should be in accordance with the latest edition of the IEE regulations (BS 7671).

### Wire Identification – Twin & Earth Cable

**EARTH** = Green/Yellow Slewing

**NEUTRAL** = Black (pre Apr 04) / Blue (after Apr 04)

**LIVE** = Red (pre Apr 04) / Brown (after Apr 04)

To prevent fire hazard always use cable of the correct rating, size and type for the application.

Note - As from 1st April 2004 new colour codes for hard wire installations was introduced.



**Technical Helpline: 03300 249 279**

**If in doubt consult a competent electrician.**

### Product Application & Features

The Weatherproof FCU comprises a robust polycarbonate enclosure with durable integrated Fused Connection Unit. It provides a convenient & safe wall-mounted power point for fixed outdoor equipment. The enclosure is IP66 rated in use, which means that when the front cover is securely closed, the sealed construction provides a very high level of protection against the ingress of both water & dust.