

DUCT TAPE

Water Resistant Duct Tape

Technical Data Sheet



TIGRIS TAPE RANGE

Description:

A water-resistant, all purpose, premium quality duct tape for binding, fixing, sealing, repairing, joining, protecting, marking and much more.

Features & Benefits:

- ◆ *Multi-purpose.*
- ◆ *Easy to tear.*
- ◆ *Water resistant.*

Uses

Rubber based adhesive provides long lasting adhesion on most substrates.

Do not use on wet or oily surfaces. It is the users responsibility to determine suitability of use.

Application

1. Ensure surfaces are clean, free from dust and dry.
2. Remove any outer packaging from roll of tape.
3. Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
4. Cut with a knife or tear when finished.

Size

48mm x 45m rolls.

Colour

Available in silver and black.

Shelf Life

Maximum 5 years from date of manufacture.

Storage Conditions

Store in original, unopened packs in dry conditions between +5°C and +25°C and keep out of direct sunlight and protect from frost.

Disposal Of Containers

Do not leave unused product or discarded materials on site where it could be harmful to children, animals or the environment. Remove to a central disposal point in accordance with local regulations.



Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Backing	PE laminated synthetic cloth
Adhesive	Synthetic rubber
Total Weight	approx 155gsm
Thickness	160 microns +/- 10%
MD Tensile Strength	75N/25mm
Adhesion to Steel Plate	16.5N/25m
Rolling Back Tack	>0.5cm
Mesh	35
Commodity Code	3919101990

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDDT45S	Silver	48mm x 45m	5056437400185	-
BDDT45BL	Black	48mm x 45m	5056437400192	-

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 4: Updated 18/09/24
Supersedes: V3 18/02/21

bond it

An **ASTRAL** Limited Company



Certificate Number 6152
ISO 9001
ISO 14001
ISO 45001

Part of the bond it tape range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com