



# Product data sheet

Power tools for trade & industry

Combi Laser

## GCL 2-15



Compact and versatile for short-distance levelling applications

### The most important data

Working range	up to 15 m
Accuracy	± 0.3 mm/m
Self-levelling range	± 4°

**Part Number** 0 601 066 E00

## Technical data

### Technical data

Laser diode	630 – 650 nm, < 1mW
Operating temperature	-10 – 50 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range	up to 15 m
Accuracy	± 0.3 mm/m
Working range of laser points, max.	10 m (top), 10 m (bottom)
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 54
Power supply	3 x 1.5 V LR6 (AA)
Operating time (max.)	6 h in cross line and point mode, 8 h in cross line mode, 12 h in line and point mode, 16 h in line mode, 22 h in point mode
Tripod thread	1/4", 5/8"
Weight, approx.	0.49 kg
Colour of laser line	red
Projection	2 lines / 2 points
Plumb point accuracy	± 0.7 mm/m



**BOSCH**

Invented for life

# Product data sheet

Power tools for trade & industry

---

## Advantages:

- Both horizontal and vertical lines are perfect for short-distance levelling applications
- Enjoy precise transfer applications thanks to two centred plumb points
- Rotating mount RM 1 Professional allows laser lines to be easily positioned around the plumb points

