

couplers – fabricated fittings

FASLOCK AUTO


■ FASLOCK AUTO – couplers

FASLOCK AUTO is used to form radius bends

- For 100 mm and 200 mm wide steel wire cable tray use FASLOCK AUTO S (small)
- For 300 mm wide to 600 mm wide tray use FASLOCK AUTO XL (large)


Supplied in packs of 25. No additional fasteners or tools required
For detailed installation instructions see p.113-115

■ Installation



FASLOCK AUTO is positioned on the internal angle of a radius bend after steel wire cable tray has been cut
No fasteners required

■ Assembly



Clip FASLOCK AUTO into place
Safety edges protect both the cables and the installer



Patented




Fast assembling



Fixing without nuts and bolts

■ Dimensions and weights

30 / 54 / 105 mm ± 0.1 100 → 600 mm



	Weight (kg)			
	EZ	ZN+	DC	316L
FASLOCK AUTO S	0-01	0-01	0-01	0-01
FASLOCK AUTO XL	0-01	0-01	0-01	0-01

Please use Cat. No. when placing your order, see p. 21

All weights are given in Kilograms (kg)

Key: **EZ** Electrogalvanised after manufacture
ZN+ Zinc nickel plus additional coating (black)

DC Zinc rich coating

316L Stainless steel 316 L

For detailed information related to finishes, refer to **p. 132-133**

All dimensions (mm) are nominal

→ Creating a radius bend : see p. 114–117

→ Installing FASLOCK AUTO : see p. 113–115