

fixing kits – length to length coupling

KITASSTR – KITASSVS – KITFIXTR – KITFIXVS – KITINOX

Use for length to length coupling. Supplied in packs of 50

■ Installation



Fixing kits can be used to join two straight lengths. Use on both side wire and base of tray


■ Assembly

The table below indicates the recommended quantity of fixing kits required to couple straight lengths together

Side coupling



Base coupling



Kit	50		100		150		200		300		400		500		600		
	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B	
CF30 - CF54	2	0	2	1	2	1	2	1	2	2	2	2	2	2	2	2	3
CF80	-	-	2	1	-	-	2	1	2	2	2	2	2	2	2	2	3
CF105	-	-	2	1	2	1	2	1	2	2	2	2	2	2	2	2	3
CF150	-	-	-	-	-	-	2	2	2	2	2	2	2	2	2	2	3
CFG	-	-	2	1	2	1	2	1	-	-	-	-	-	-	-	-	-
HDF105	-	-	2	1	2	1	2	1	2	2	2	2	2	2	2	2	3

→ Straight lengths : see p. 44-55

→ Creating bends, tees and reducers : see p. 114-127

■ Dimensions and weights

KITASSTR



KITFIXVS



KITASSVS



KITINOX



KITFIXTR



	Weight (kg)				
	EZ	ZN+	DC	304L	316L
KITASSTR	0-03	0-03	0-03	-	0-03
KITASSVS	0-03	-	0-03	-	-
KITFIXTR	0.02	-	0-02	-	-
KITFIXVS	0.02	-	0-02	-	-
KITINOX	-	-	-	-	0-03
CE25	0-01	-	0-01	0-01	0-01
CE30	0-01	-	0-01	0-01	0-01
BTRCC6 x 20	0-01	-	0-01	0-01	0-01

Please use Cat. No. when placing your order, see p. 23

All weights are given in Kilograms (kg)

Key: EZ Electrogalvanised after manufacture
ZN+ Zinc nickel plus additional coating (black)
DC Zinc rich coating

304L Stainless steel 304 L
316L Stainless steel 316 L

For detailed information related to finishes, refer to p. 132-133

All dimensions (mm) are nominal