

F-P

ROUND PIN TERMINAL, PRE-INSULATED WITH PVC, FOR COPPER CONDUCTORS



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20°C
Maximum operating temperature	75°C
Threshold of operating temperature for short periods	90°C
Type of insulation	partial
Easy insertion input	Yes
Surface treatment	tin plating
Crimping geometry	radial

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Insulated cover material	Polyvinylchloride PVC
Annealing	Yes

WEIGHT AND DIMENSIONS

Tip type	pin
----------	-----

LOGISTIC


Unit in minimal packaging	100PCE
---------------------------	--------

CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
--	----



RF-P		Insulated cover colour red			Range of cable cross section [mm ²] 0.25							
tipo	B [mm]	P [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	ROHS compliant	
RF-P8	1.6	7.8	17.8	4.2	10.1	4	5.5	1.8	5	3000	Yes	
RF-P10	1.6	9.8	19.8	4.2	10.1	4	5.5	1.8	5	3000	Yes	
RF-P12	1.6	12	22	4.2	10.1	4	5.5	1.8	5	3000	Yes	

BF-P		Insulated cover colour blue			Range of cable cross section [mm ²] 1.5							
tipo	B [mm]	P [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	ROHS compliant	
BF-P8	1.6	7.8	17.8	4.2	10.1	4.9	6.4	2.4	5	2500	Yes	
BF-P10	1.6	9.8	19.8	4.2	10.1	4.9	6.4	2.4	5	2500	Yes	
BF-P12	1.6	11.8	21.8	4.2	10.1	4.9	6.4	2.4	5	2500	Yes	

GF-P		Insulated cover colour yellow			Range of cable cross section [mm ²] 4							
tipo	B [mm]	P [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	ROHS compliant	
GF-P10	2.2	10.4	24.5	8	14.1	6.6	8.1	3.6	7	1000	Yes	
GF-P12	2.2	12.6	26.7	8	14.1	6.6	8.1	3.6	7	1000	Yes	
GF-P14	2.2	14.6	28.7	8	14.1	6.6	8.1	3.6	7	1000	Yes	