

High Impact Conduit

- Manufactured in accordance to: BS 4607 Part 5; BSEN 50086-2-1 (1996); BSEN 61386-21 (2004) formerly BS 6099.
- Tested regularly to high quality standards, the Centaur super high impact conduit provides an easy and secure method of cable management.
- Heavy gauge and light gauge options are available to suit a variety of applications.



HG 20W

Super High Impact Conduit, Heavy Gauge

Size	Nom. Wall Thickness	Cat. No.	Pack Quantity
20mm	1.8mm	HG 20*	30 x 3m
25mm	1.9mm	HG 25*	30 x 3m
32mm	2.5mm	HG 32	10 x 3m
38mm	2.5mm	HG 38	10 x 3m
50mm	3.2mm	HG 50	10 x 3m

* - Selected conduit & accessories also available in red.



LG 20W

Super High Impact Conduit, Light Gauge

Size	Nom. Wall Thickness	Cat. No.	Pack Quantity
20mm	1.2mm	LG 20	30 x 3m
25mm	1.5mm	LG 25	30 x 3m
32mm	1.5mm	LG 32	10 x 3m
38mm	1.5mm	LG 38	10 x 3m
50mm	1.8mm	LG 50	10 x 3m



OCO 1500W

High Impact Oval Conduit

Size	Nom. Wall Thickness	Cat. No.	Pack Quantity
13mm	0.8mm	OCO 500W	50 x 3m
16mm	0.8mm	OCO 625W	50 x 3m
20mm	0.8mm	OCO 750W	50 x 3m
25mm	1.0mm	OCO 1000W	50 x 3m
32mm	1.0mm	OCO 1250W	20 x 3m
38mm	1.3mm	OCO 1500W	20 x 3m

Manufactured to comply with BS 4607 Part 5.



CH 150W

High Impact Channels

Size	Nom. Wall Thickness	Cat. No.	Pack Quantity
13mm	7.4mm	CH 050W	50 x 2m
25mm	8.0mm	CH 100W	50 x 2m
38mm	8.5mm	CH 150W	50 x 2m

Conduit & accessories available as standard black or white.