



Linktree*

HD WIRED PoE IP CAMERAS

CHIPCAM11 / CHIPCAM12

Data Sheet

5MP HD IP VARIFOCAL BULLET CAMERAS



CHIPCAM11



CHIPCAM12

FEATURES

- IR night vision
- Power over Ethernet [PoE]
- ONVIF compliant
- 2.7-13.5mm varifocal lens
- 12V DC power port
- 3 year warranty





HD WIRED PoE IP CAMERAS

CHIPCAM11 / CHIPCAM12

Data Sheet

	PART CODE	CHIPCAM11	CHIPCAM12
Camera Specs	Camera Casing Colour	White	Black
Video	Imaging Device	1/2.7"	1/2.7"
Lens Type	Effective Pixels	5MP 2592(H)×1944(V)	5MP 2592(H)×1944(V)
	Scanning System	Progressive CMOS	Progressive CMOS
	Min. Illumination	Color 0.003lux @ F1.6(AGC ON); B/W 0 lux @ IR ON	Color 0.003lux @ F1.6(AGC ON); B/W 0 lux @ IR ON
	Focal Length (Zoom Ratio)	2.7-13.5mm	2.7-13.5mm
	Max. Aperture Ratio	F No. 1.8 (W) ~ 3.3(T)	F No. 1.8 (W) ~ 3.3(T)
	Angular Field of View	Horizontal: 31 ~102°, Vertical: 23 ~ 73°, Diagonal: 38 ~ 138°	Horizontal: 31 ~102°, Vertical: 23 ~ 73°, Diagonal: 38 ~ 138°
	Min. Object Distance	0.3m-INF	0.3m-INF
	Lens Type	Motorized(Ø14)	Motorized(Ø14)
Operational	IR Viewable Length	Up to 45m	Up to 45m
	Camera Title	On/Off	On/Off
	Day & Night	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)
	Backlight Compensation	Off/On (5 Zone)	Off/On (5 Zone)
	Wide Dynamic Range	WDR	WDR
	Digital Noise Reduction	3D DNR	3D DNR
	Motion Detection	Off/On (8 Level)	Off/On (8 Level)
	Privacy Masking	Off/On (4 Zone, Rectangle)	Off/On (4 Zone, Rectangle)
	Gain Control	Auto	Auto
	White Balance	Auto/Manual	Auto/Manual
	Electronic Shutter Speed	1/5 ~ 1/20000s	1/5 ~ 1/20000s
	On-Board Storage	Micro SD slot, up to 256GB	Micro SD slot, up to 256GB
	Alarm	1 input, 1 output	1 input, 1 output
	Audio	1 input (RCA), 1 output (RCA)	1 input (RCA), 1 output (RCA)
	Hardware Reset	Yes	Yes
	Smart Feature	"Face Recognition(FR) Human&Vehicle Detection(PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD) Cross Counting(CC) Stationary Object Detection(SOD) Heat Map(HM) Crowd Density Detection(CD) Queue Length Detection(QD) license Plate Detection(LPD) Rare Sound Detection(RSD)"	"Face Recognition(FR) Human&Vehicle Detection(PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD) Cross Counting(CC) Stationary Object Detection(SOD) Heat Map(HM) Crowd Density Detection(CD) Queue Length Detection(QD) license Plate Detection(LPD) Rare Sound Detection(RSD)"





HD WIRED PoE IP CAMERAS

CHIPCAM11 / CHIPCAM12

Data Sheet

	PART CODE	CHIPCAM11	CHIPCAM12
Network	Ethernet	RJ45(10/100BASE-T)	RJ45(10/100BASE-T)
	Video Compression Format	H.265/H.264	H.265/H.264
	Resolution	"Main Stream @30fps 5MP(2592x1944), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960) Sub Stream @30fps 1080P(1920x1080) 720P(1280x720),VGA(640x480) Mobile Stream @30fps VGA(640x480), QVGA(320x240)"	"Main Stream @30fps 5MP(2592x1944), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960) Sub Stream @30fps 1080P(1920x1080) 720P(1280x720),VGA(640x480) Mobile Stream @30fps VGA(640x480), QVGA(320x240)"
	Video Quality Adjustment	256Kbps ~ 8Mbps	256Kbps ~ 8Mbps
	Bitrate control method	CBR/VBR	CBR/VBR
	Streaming Capability	Triple-Stream(Main/Sub/Moile)	Triple-Stream(Main/Sub/Moile)
	Protocol	"TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP"	"TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP"
	Web browser	"IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above"	"IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above"
	Security	IP address filter;complicated password;Authenticated username and password	IP address filter;complicated password;Authenticated username and password
	Streaming Method	Unicast/Multicast	Unicast/Multicast
	Application Programming Interface	ONVIF(Profile S/G/T)	ONVIF(Profile S/G/T)
Environmental	Operation Conditions	-35~+60°C/less than ≤ 90% RH	-35~+60°C/less than ≤ 90% RH
	IP67	IP67	IP67
Electrical	Input Voltage / Current	D12V/POE(IEEE802.3af)	D12V/POE(IEEE802.3af)
	Power Consumption(IR OFF)	3.5W-4.5W	3.5W-4.5W
	Power Consumption(IR ON)	7.5W-9.5W	7.5W-9.5W
Mechanical	Material	Metal	Metal
	Dimensions (HxWxD)	242*87.4*83.88mm	242*87.4*83.88mm
	Weight	811g	811g

