



4K WIRED POE IP CAMERAS

CHIPCAM22 & CHIPCAM23

[Data Sheet](#)

8MP ULTRA HD IP FIXED LENS BULLET CAMERAS



CHIPCAM22



CHIPCAM23

FEATURES

- IR night vision
- Power over Ethernet [PoE]
- ONVIF compliant
- 2.8mm fixed lens
- 12V DC power port
- 3 year warranty





4K WIRED POE IP CAMERAS

CHIPCAM22 & CHIPCAM23

Data Sheet

	PART CODE	CHIPCAM22	CHIPCAM23
Camera Specs	Camera Casing colour	White	Black
Video	Imaging Device	1/2.7"	1/2.7"
Lens Type	Effective Pixels	8MP 3840(H)×2160(V)	8MP 3840(H)×2160(V)
	Scanning System	Progressive CMOS	Progressive CMOS
	Min. Illumination	Color 0.009lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON	Color 0.009lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
	Lens Type		
Operational	Focal Length (Zoom Ratio)	2.8mm	2.8mm
	Max. Aperture Ratio	F No. 1.6	F No. 1.6
	Angular Field of View	Horizontal: 110°, Vertical: 58°, Diagonal: 132°	Horizontal: 110°, Vertical: 58°, Diagonal: 132°
	Min. Object Distance	1.8m	1.8m
	Lens Type	Fixed(M12)	Fixed(M12)
	Operational		
	IR Viewable Length	Up to 30m	Up to 30m
	Camera Title	On/Off	On/Off
	Day & Night	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)
	Backlight Compensation	Off/On (5 Zone)	Off/On (5 Zone)
	Wide Dynamic Range	DWDR	DWDR
	Digital Noise Reduction	3D DNR	3D DNR
	Motion Detection	Off/On (8 Level)	Off/On (8 Level)
	Privacy Masking	Off/On (4 Zone, Rectangle)	Off/On (4 Zone, Rectangle)
	Gain Control	Auto	Auto
	White Balance	Auto/Manual	Auto/Manual
	Electronic Shutter Speed	1/5 ~ 1/20000s	1/5 ~ 1/20000s
	On-Board Storage	Micro SD slot, up to 256GB	Micro SD slot, up to 256GB
	Alarm	NA	NA
	Audio	Built-in microphone	Built-in microphone
	Hardware Reset	Yes	Yes
	Smart Feature	Face Recognition(FR) Human&Vehicle Detection(PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD) Cross Counting(CC) Stationary Object Detection(SOD) Heat Map(HM) Crowd Density Detection(CD) Queue Length Detection(QD) license Plate Detection(LPD) Rare Sound Detection(RSD)	Face Recognition(FR) Human&Vehicle Detection(PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD) Cross Counting(CC) Stationary Object Detection(SOD) Heat Map(HM) Crowd Density Detection(CD) Queue Length Detection(QD) license Plate Detection(LPD) Rare Sound Detection(RSD)





4K WIRED POE IP CAMERAS

CHIPCAM22 & CHIPCAM23

Data Sheet

	PART CODE	CHIPCAM22	CHIPCAM23
Network	Ethernet	RJ45(10/100BASE-T)	RJ45(10/100BASE-T)
	Video Compression Format	H.265/H.264	H.265/H.264
	Resolution	Main Stream @25fps 8MP(3840x2160), 5MP(2592x1944,3072x1728), 4MP(2592x1520), 3MP(2304x1296),1080P(1920x1080), 960P(1280*960),720P(1280x720), Sub Stream @25fps 720P(1280x720),VGA(640x480), QVGA(320x240) Mobile Stream @25fps VGA(640x480), QVGA(320x240)	Main Stream @25fps 8MP(3840x2160), 5MP(2592x1944,3072x1728), 4MP(2592x1520),3MP(2304x1296), 1080P(1920x1080), 960P(1280*960), 720P(1280x720), Sub Stream @25fps 720P(1280x720),VGA(640x480), QVGA(320x240) Mobile Stream @25fps VGA(640x480), QVGA(320x240)
	Video Quality Ajustment	256Kbps ~ 16Mbps	256Kbps ~ 16Mbps
	Bitrate control method	CBR/VBR	CBR/VBR
	Streaming Capability	Triple-Stream(Main/Sub/Moile)	Triple-Stream(Main/Sub/Moile)
	Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
	Web browser	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
	Security	IP address filter; complicated password; Authenticated username and password	IP address filter; complicated password; Authenticated username and password
	Streaming Method	Unicast/Multicast	Unicast/Multicast
	Application Programming Interface	ONVIF(Profile S/G/T)	ONVIF(Profile S/G/T)
Environmental	Operating Conditions	-35~+60°C/less than ≤ 90% RH	-35~+60°C/less than ≤ 90% RH
Electrical	Ingress Protection	IP67	IP67
	Input Voltage / Current	D12V/POE(IEEE802.3af)	D12V/POE(IEEE802.3af)
Mechanical	Power Consumption	PBD	PBD
	Material	Metal	Metal
	Dimensions (HxWxD)	135.56*135.56*127mm	135.56*135.56*127mm
	Weight	846g	846g

