



HD WIRED PoE IP CAMERAS

CHIPCAM3 / CHIPCAM4

[Data Sheet](#)

5MP HD IP FIXED LENS BULLET CAMERAS



CHIPCAM3



CHIPCAM4

FEATURES

- IR night vision
- Power over Ethernet [PoE]
- ONVIF compliant
- 2.8mm fixed lens
- 12V DC power port
- 3 year warranty





HD WIRED PoE IP CAMERAS

CHIPCAM3 / CHIPCAM4

Data Sheet

	PART CODE	CHIPCAM3	CHIPCAM4
Camera Specs	Camera Casing Colour	White	Black
	Video		
Lens Type	Imaging Device	1/2.7"	1/2.7"
	Effective Pixels	5MP 2592(H)×1944(V)	5MP 2592(H)×1944(V)
	Scanning System	Progressive CMOS	Progressive CMOS
	Min. Illumination	Color 0.003lux @ F1.6(AGC ON); B/W 0 lux @ IR ON	Color 0.003lux @ F1.6(AGC ON); B/W 0 lux @ IR ON
	Focal Length (Zoom Ratio)	2.8mm	2.8mm
	Max. Aperture Ratio	F No. 1.6	F No. 1.6
	Angular Field of View	Horizontal: 97°, Vertical: 70°, Diagonal: 128°	Horizontal: 97°, Vertical: 70°, Diagonal: 128°
	Min. Object Distance	1.8m	1.8m
Operational	Lens Type	Fixed(M12)	Fixed(M12)
	IR Viewable Length	Up to 30m	Up to 30m
Operational	Camera Title	On/Off	On/Off
	Day & Night	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)
	Backlight Compensation	Off/On (5 Zone)	Off/On (5 Zone)
	Wide Dynamic Range	WDR	WDR
	Digital Noise Reduction	3D DNR	3D DNR
	Motion Detection	Off/On (8 Level)	Off/On (8 Level)
	Privacy Masking	Off/On (4 Zone, Rectangle)	Off/On (4 Zone, Rectangle)
	Gain Control	Auto	Auto
	White Balance	Auto/Manual	Auto/Manual
	Electronic Shutter Speed	1/5 ~ 1/20000s	1/5 ~ 1/20000s
	On-Board Storage	Micro SD slot, up to 256GB	Micro SD slot, up to 256GB
	Alarm	NA	NA
	Audio	Built-in microphone	Built-in microphone
	Hardware Reset	Yes	Yes
	Smart Feature	"Face Recognition(FR) Human&Vehicle Detection(PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD) Cross Counting(CC) Stationary Object Detection(SOD) Heat Map(HM) Crowd Density Detection(CD) Queue Length Detection(QD) license Plate Detection(LPD) Rare Sound Detection(RSD)"	"Face Recognition(FR) Human&Vehicle Detection(PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD) Cross Counting(CC) Stationary Object Detection(SOD) Heat Map(HM) Crowd Density Detection(CD) Queue Length Detection(QD) license Plate Detection(LPD) Rare Sound Detection(RSD)"





HD WIRED PoE IP CAMERAS

CHIPCAM3 / CHIPCAM4

Data Sheet

	PART CODE	CHIPCAM3	CHIPCAM4
Network	Ethernet	RJ45(10/100BASE-T)	RJ45(10/100BASE-T)
	Video Compression Format	H.265/H.264	H.265/H.264
	Resolution	"Main Stream @30fps 5MP(2592x1944), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960) Sub Stream @30fps 1080P(1920x1080) 720P(1280x720),VGA(640x480) Mobile Stream @30fps VGA(640x480), QVGA(320x240)"	"Main Stream @30fps 5MP(2592x1944), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960) Sub Stream @30fps 1080P(1920x1080) 720P(1280x720),VGA(640x480) Mobile Stream @30fps VGA(640x480), QVGA(320x240)"
	Video Quality Adjustment	256Kbps ~ 8Mbps	256Kbps ~ 8Mbps
	Bitrate control method	CBR/VBR	CBR/VBR
	Streaming Capability	Triple-Stream(Main/Sub/Moile)	Triple-Stream(Main/Sub/Moile)
	Protocol	"TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP"	"TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP"
	Web browser	"IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above"	"IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above"
	Security	IP address filter;complicated password;Authenticated username and password	IP address filter;complicated password;Authenticated username and password
	Streaming Method	Unicast/Multicast	Unicast/Multicast
	Application Programming Interface	ONVIF(Profile S/G/T)	ONVIF(Profile S/G/T)
Environmental	Operating Conditions	-35~+60°C/less than ≤ 90% RH	-35~+60°C/less than ≤ 90% RH
	Ingress Protection	IP67	IP67
Electrical	Input Voltage / Current	D12V/POE(IEEE802.3af)	D12V/POE(IEEE802.3af)
	Power Consumption(IR OFF)	2.5W-3.5W	2.5W-3.5W
	Power Consumption(IR ON)	4.5W-6W	4.5W-6W
Mechanical	Material	Metal	Metal
	Dimensions (HxWxD)	150.8*70.9*70.9mm	150.8*70.9*70.9mm
	Weight	400g	400g

