

IKALL SIMPLEBUS AUDIO SPEAKER

Audio speaker unit complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP switch with 8 positions for programming user calls. 33Vdc from power supply unit part. 1595. On-board electronic lock-release function (3A), plus a 10A relay. Timed lock-release inputs and door open indication.. For use in modules part. 33400, 33401 and 33402. Compatible with all SBTOP functions and products. Dimensions: 102x55x38 mm.



Main specifications

Simplebus Top system:	Yes
Compatible with the Building Kit System:	No
Vip system:	No
Audio system:	Yes
Audio/video system:	Yes
Clamps:	L L V+ V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25÷55

Functions

Key button function:	Yes
----------------------	-----

General info

Product height (mm):	55
Product width (mm):	104
Product depth (mm):	35

Compatibility

Simplebus 2 system:	Yes
---------------------	-----

Packaging

Single pack height (mm):	53
Single pack width (mm):	110
Single pack weight (Kg):	0,193
Single pack depth (mm):	94

DATA SHEET

Single pack volume (dm3):

0,548