

NSW Approved Point of Attachment Brackets

'B' RATED SINGLE LEG BRACKETS

Suitable for single or three phase aluminium aerial service lines up to approx. 30m in length.

For exact details regarding required bracket strength ratings for particular applications, please refer to the New South Wales Service & Installation Rules, your local Supply Authority or Service Provider.

For applications where the service line will be pulling on the bracket at an angle greater than 45° it is recommended that a "D" Rated double leg bracket is used to avoid twisting the bracket mounting.



CAT No.	NOMINAL HEIGHT	APPLICATION
---------	----------------	-------------

CI 2B1F	300mm	Fascia mount for fixing to fascia under gutter. Must be bolted through hardwood noggin of adequate strength fixed between rafters directly behind fascia board or using Clarke fascia support bracket (Part no. CI SB1/LH or /RH) M12 galvanised bolts required for fixing (not supplied)
CI 3B1F	450mm	
CI 4B1F	600mm	
CI 5B1F	750mm	
CI 6B1F	900mm	



CI 2B1R	300mm	Rafter mount for fixing to rafters behind a fascia board and flashed around penetration through roofing material. 2 x M10 galvanised rafter fixing bolts supplied. For ease of installation see Ease of Installation Products.
CI 3B1R	450mm	
CI 4B1R	600mm	
CI 5B1R	750mm	
CI 6B1R	900mm	

P: 02 9522 7800 F: 02 9522 7900
E: sales@clarkeind.com.au