



CCFLED

Cleverfit Exit, Surface Mount, LP, Clevertest Plus, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CCFLED
MIC	AUA02310030002
Description	Cleverfit Exit, Surface Mount, LP, Clevertest Plus, All Pictograms, Single or Double Sided
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall & Ceiling, Single-Sided & Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.6kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All Directional Inserts Included in the Box
Lamp(s)	6 x LED, Lifetime: >100,000hrs (AS/NZS2293.3 LSL=12Y/00M)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.7 Watts (Max)
Inrush Current (Peak/Duration)	11.26A/80µS
Earth Leakage	N/A (Class II)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
AS2293 Classification	C0=D4 C90=E3.2
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	☒ Class II double insulated,  noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002348	Driver
8002710	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.