



EUBPRO-SM-LI

Ultrablade Pro Exit, Surface Mount, Trade Series, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	EUBPRO-SM-LI
MIC	AUA03510090001
Description	Ultrablade Pro Exit, Surface Mount, Trade Series, All Pictograms, Single or Double Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0 kg
Operating Mode	Can be toggled between maintained and non-maintained mode by pressing the test button 5 times within a 4 second period – default setting is maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x LED, 50,000 hours
Projected Life Source Life (LSL)	20Y/00M
Operating Voltage	240V AC; 50Hz
Power Consumption	1.8 Watts (Standby), 2.8 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560200	BATT:EcoLith 3.2V 1.1Ah 210mm lead,noBKT
8002179	PCA:EUBPRO LED Strip Assy (CT10602-x)
8002979	PCA: EUBPRO-SM-LI #CT10614-L2 6C50 M/NM

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.