

Product datasheet

Specifications



Machined Lock Ring, Clipsal - Cable Management, 40mm Male to 32mm Female Steel Reducer

1264S4M

Main

Product brand	Clipsal
Range of product	Series 1264

Complementary

Material	Steel
Product destination	diameter: 32 mm tube diameter: 40 mm tube
Length	42 mm

Environment

Standards	AS 2052 AS 1721
-----------	--------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	4.2 cm
Package 1 Length	4.2 cm
Package 1 Weight	83 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	7 cm
Package 2 Width	10.7 cm
Package 2 Length	14 cm
Package 2 Weight	20 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level 0

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No