

# Product datasheet

Specifications

**CLIPSAL**



## Socket Inlet, Standard Series, 3 PIN, 15A, 250V, IP34, Weatherproof Flap

435VFS15-WE

### Main

Product brand Clipsal

### Complementary

[In] rated current 15 A

[Ue] rated operational voltage 230 V 50/60 Hz conforming to EN 60309-2

Colour White electric

Material Plastic

Connections - terminals Screw terminal

Plug, socket, control station shape Straight

Duration 6 h

### Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 7.8 cm

Package 1 Width 9.5 cm

Package 1 Length 13 cm

Package 1 Weight 128 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
---	---

## Use Better

### Materials and Substances

Recycled metal content at CR level	0
------------------------------------	---

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
-----------------------------------	---------------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

## Use Again

### Repack and remanufacture

Take-back	No
-----------	----