

## Product data sheet

### Characteristics

# 4TC

## Timer, Clipsal - Max 4, 16 A 250 V 1 module 24 hour analog



### Main

Range of product	Power
Product brand	Clipsal

### Complementary

[Ue] rated operational voltage	250 V AC
Rated current	16 A
Mounting support	DIN rail

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	9.4 cm
Package 1 Length	7.5 cm
Package 1 Weight	87 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	8.3 cm
Package 2 Width	10.1 cm
Package 2 Length	27.3 cm
Package 2 Weight	1 kg

### Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.