

Product datasheet

Specifications

CLIPSAL



Mains Connection Box, Clipsal - Cable Management, Unfused, 2 Terminal, 20mm Screwed Entry

645/2-BK

Main

Colour	Black
Product brand	Clipsal
Provided equipment	Cover
Cover type	Transparent

Complementary

Colour code	BK
Number of clamp	2
fixing mode	By screws
Cable entry number	1
Material	PA (polyamide) 6

Environment

IP degree of protection	IP30
Dust zone	-

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	6.6 cm
Package 1 Length	6.8 cm
Package 1 Weight	118 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	77 cm
Package 2 Width	138 cm
Package 2 Length	239 cm
Package 2 Weight	1.28 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	245 cm

Package 3 Width	253 cm
Package 3 Length	298 cm
Package 3 Weight	6.4 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

Compliant with Exemptions

SCIP Number

C6f2fabe-d5ba-4588-bd03-c90f7def1381

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

No need of specific recycling operations

Take-back

No