

## HEAVY DUTY LINKS

### BP165/7

500V 165A 7 Hole Link.



BP165/7

### BP165/7ETP

500V 165A 7 Hole Link with tin-plate link and screws. Two screws per tunnel. Black unbreakable, transparent polycarbonate base and cover.

Dimensions: 100 x 43 x 40mm.  
Terminal bar: 16 x 16 x 76mm.  
2 tunnels: 9.5mm diameter accommodate 50mm<sup>2</sup> cables.  
1 tunnel: 8.0mm diameter accommodates 35mm<sup>2</sup> cable.  
2 tunnels: 7.1mm diameter accommodate 25mm<sup>2</sup> cables.  
2 tunnels: 5.5mm diameter accommodate 16mm<sup>2</sup> cables.  
Mounting centres: 71 x 29mm.  
Available in red.

### BP165/7BW

500V 165A 7 Hole Back Wiring Link.

2 terminal tunnels: 9.5mm diameter accommodate 50mm<sup>2</sup> cable, have single screw connection.  
5 remaining terminals have 2 screws per tunnel. See BP165/7 above.  
Temperature rating: 120°C maximum.

### BP165/13

500V 165A 13 Hole Link. Two screws per tunnel. Black unbreakable, transparent polycarbonate base and cover.

Dimensions: 120 x 47 x 52mm.  
Terminal Bar: 19 x 16 x 95.3mm.  
2 tunnels: 9.5mm diameter accommodate 50mm<sup>2</sup> cable.  
5 tunnels: 6.4mm diameter accommodate 16mm<sup>2</sup> cable.  
6 tunnels: 4.8mm diameter accommodate 10mm<sup>2</sup> cable.  
Mounting centres: 90 x 34mm.  
Available in red.  
Temperature rating: 125°C maximum.



BP165/13

### BP165/13ETP

Same as BP165/13 with electro tin-plate link and screws.

### BP350/7

500V 7 Hole Link. Incoming cables clamped with single grub screw. Supplied with Allen key. Two screws per take off tunnel. Black base and cover.

Dimensions: 120 x 47 x 52mm.  
Terminal bar: 25.4 x 19 x 95.3mm.  
2 tunnels: 15.0mm diameter accommodate 120mm<sup>2</sup> cables.  
2 tunnels: 9.5mm diameter accommodate 50mm<sup>2</sup> cables.  
2 tunnels: 8.0mm diameter accommodate 35mm<sup>2</sup> cables.  
1 tunnel: 5.5mm diameter accommodates 16mm<sup>2</sup> cables.  
Mounting centres: 90 x 34mm.  
Available in red.  
Temperature rating 125°C maximum.



BP350/7

### BP350/7ETP

Same as BP350/7 with electro tin-plate link and screws.

### BP350/13

500V 13 Hole Link. Incoming cables clamped with single grub screw. Supplied with Allen key. Two screws per take off tunnel. Black unbreakable, transparent polycarbonate base and cover.

Dimensions: 120 x 47 x 52mm.  
Terminal bar: 25.4 x 19 x 95.3mm.  
2 tunnels: 15.0mm diameter accommodate 120mm<sup>2</sup> cables.  
1 tunnel: 8.0mm diameter accommodates 35mm<sup>2</sup> cable.  
8 tunnels: 5.5mm diameter accommodate 16mm<sup>2</sup> cable.  
2 tunnels: 4.8mm diameter accommodate 10mm<sup>2</sup>.  
Mounting centres: 90 x 34mm.  
Available in red.  
Temperature rating: 125°C maximum.



BP350/13

### BP350/13ETP

Same as BP350/13 with electro tin-plate link and screws.