

# Product datasheet

Specifications

**CLIPSAL**



Twin switched socket, Medilec, 20A RCD protected, Clipsal, 10A, horizontal, antibacterial, dark blue

MLP3025PA-DB

## Main

Range of product	Medilec
Range	Medilec
Product or component type	Switched socket
Product brand	Clipsal
Assembly Type	Complete device
Colour tint	Dark blue
Protection	Shuttered
Main colour tint	Dark blue

## Complementary

control type	Rocker
Number of gangs	2 gangs
Pin number	3
Number Of Outlets	2
Actuator	Switch
Socket-outlet type	Double socket-outlet
Mounting Type	Screw
Local signalling	Indicator LED
Installation Type	Wall mounted
Installation Orientation	Horizontal
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Type of installation	Indoor installation
[Ue] rated operational voltage	230...240 V AC
Network frequency	50 Hz
[In] rated current	10 A
Connections - terminals	4 x 2.5 mm <sup>2</sup> screw terminal 3 x 4 mm <sup>2</sup> screw terminal 3 x 4 mm <sup>2</sup>
Embedding depth	34.6 mm
Depth	43.6 mm
Height	78.2 mm

<b>Width</b>	116 mm
<b>Mounting Centers</b>	84 mm
<b>Earth-leakage protection class</b>	Type I Type A
<b>Net Weight</b>	100 g
<b>surface treatment</b>	Antibacterial
<b>Screwdriver shape</b>	Philips No 2 Square drive no 1 (SQ1)
<b>Wire stripping length</b>	16 mm
<b>Number of power socket outlets</b>	2 x 1P + E, Australian/New Zealand
<b>Cover Thickness</b>	9 mm
<b>Number Of Switches</b>	2

## Environment

<b>IP degree of protection</b>	IP20
<b>Product certifications</b>	RCM
<b>Standards</b>	AS/NZS 3190 AS/NZS 3100 ISO 22196
<b>Relative humidity</b>	10...95 %
<b>Ambient air temperature for operation</b>	0...45 °C
<b>Environmental characteristic</b>	Indoor use

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.1 cm
<b>Package 1 Width</b>	8.1 cm
<b>Package 1 Length</b>	12.6 cm
<b>Package 1 Weight</b>	100 g
<b>Unit Type of Package 2</b>	CAR
<b>Number of Units in Package 2</b>	32
<b>Package 2 Height</b>	22.4 cm
<b>Package 2 Width</b>	26.1 cm
<b>Package 2 Length</b>	33.5 cm
<b>Package 2 Weight</b>	3.4 kg
<b>Unit Type of Package 3</b>	PAL
<b>Number of Units in Package 3</b>	1536
<b>Package 3 Height</b>	95 cm
<b>Package 3 Width</b>	114 cm
<b>Package 3 Length</b>	114 cm
<b>Package 3 Weight</b>	184.2 kg

# Contractual warranty

---

Warranty

2 years

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 23

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Image of product / Alternate images

Alternative

---







