

Product datasheet

Specifications

CLIPSAL



Twin switched socket, Medilec, Clipsal, 20A for RCD, 10mA, 10A, horizontal, antibacterial, red

MLP3025RCD10A-RD

Main

Range of product	Medilec
Range	Medilec
Product or component type	RCD socket
Product brand	Clipsal
Assembly Type	Complete device
Device application	Residual current device
Colour tint	Red
Protection	Shuttered
Main colour tint	Red

Complementary

control type	Rocker
Number of gangs	2 gangs
Pin number	3
Number Of Outlets	2
Actuator	Switch Rocker
Socket-outlet type	Double socket-outlet
Mounting Type	Screw
Local signalling	Indicator LED
Installation Type	Wall mounted
Installation Orientation	Horizontal
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Type of installation	Indoor installation
[Ue] rated operational voltage	230...240 V AC
Network frequency	50 Hz
[In] rated current	10 A
Connections - terminals	4 x 2.5 mm ² screw terminal 3 x 4 mm ² screw terminal 3 x 4 mm ²
Embedding depth	34.6 mm
Depth	43.6 mm

Height	78.2 mm
Width	116 mm
Mounting Centers	84 mm
Earth-leakage protection class	Type I Type A
Net Weight	188 g
Trip unit rating	10 mA
surface treatment	Antibacterial
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Wire stripping length	16 mm
Number of power socket outlets	2 x 2P + E, Australian/New Zealand
Cover Thickness	9 mm
Number Of Switches	2
Earth-leakage sensitivity	10 mA

Environment

IP degree of protection	IP20
Product certifications	RCM
Standards	AS/NZS 3190 AS/NZS 3100 ISO 22196
Relative humidity	10...95 %
Ambient air temperature for operation	0...45 °C
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	8.1 cm
Package 1 Length	12.6 cm
Package 1 Weight	213 g
Unit Type of Package 2	CAR
Number of Units in Package 2	32
Package 2 Height	22.4 cm
Package 2 Width	26.1 cm
Package 2 Length	33.5 cm
Package 2 Weight	6.5 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1536
Package 3 Height	95 cm
Package 3 Width	114 cm

Package 3 Length	114 cm
------------------	--------

Package 3 Weight	334.8 kg
------------------	----------

Contractual warranty

Warranty	2 years
----------	---------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **182**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#) **Compliant with Exemptions**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Image of product / Alternate images

Alternative







