

## Product data sheet

### Characteristics

# MX9B124P

## Clipsal MAX9, Pin Type Comb Busbar, 1P, 100 A, 24 Modules



### Main

Product brand	Clipsal
Range	MAX9
Product or component type	Comb busbar
Total number of 18 mm modules	24

### Complementary

Number of ways	24 ways L
Poles configuration	24 x 1P
Connection pitch	18 mm
Insulation	Insulated
Device presentation	Cuttable
Provided components	2 end-pieces Tooth covers
[Ie] rated operational current	100 A
[Ue] rated operational voltage	230 V AC
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Top
Height	17 mm
Width	423 mm
Depth	15 mm
Colour	Grey (RAL 9003)

### Environment

Standards	AS/NZS 61439-3 AS/NZS 3000
Fire resistance	960 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.4 cm
Package 1 Width	2.1 cm
Package 1 Length	42.7 cm
Package 1 Weight	106.0 g
Unit Type of Package 2	CAR

Number of Units in Package 2	50
Package 2 Height	9.5 cm
Package 2 Width	10.5 cm
Package 2 Length	103.0 cm
Package 2 Weight	5.3 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	7-year
----------	--------