

# Product datasheet

Specifications



## Pin Type Comb Busbar, MAX9, 1P, 100 A, 57 Modules



MX9B157P

### Main

Product brand	Clipsal
Range	MAX9
Product or component type	Comb busbar
Total number of 18 mm modules	57

### Complementary

Number of ways	57 ways L
Poles configuration	57 x 1P
Connection pitch	18 mm
Insulation	Insulated
Device presentation	Cuttable
Provided components	10 end-pieces tooth covers
[Ie] rated operational current	100 A
[Ue] rated operational voltage	230 V AC
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Top
Height	15 mm
Width	920 mm
Depth	15 mm
Colour	Grey

### Environment

Standards	AS/NZS 61439-3 AS/NZS 3000
Fire resistance	960 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm

Package 1 Width	1.0 cm
Package 1 Length	99.0 cm
Package 1 Weight	220.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	9.5 cm
Package 2 Width	10.5 cm
Package 2 Length	103.0 cm
Package 2 Weight	6.1 kg

## Contractual warranty

Warranty	7-year
----------	--------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant

SCIP Number

41a8b1b0-6424-4682-ac9c-98796ac87431

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile

No need of specific recycling operations

Take-back

No