

Product data sheet

Characteristics

MX9E3318F

Switchboard Enclosure, MAX9, Type 3, 3 Row, 54 Ways, Flush Mounted



Main

| | |
|---------------------------------|---|
| Range | MAX9 |
| Product brand | Clipsal |
| Product or component type | Enclosure |
| Device application | Distribution |
| Number of 18 mm modules per row | 18 |
| Provided equipment | Earthing bar Neutral bar Circuit identification label Blanking plate |
| Colour | White electric (RAL 9003) |
| Door type | Plain door - reversible |

Complementary

| | |
|--------------------------------|---|
| Enclosure mounting | Flush |
| Number of horizontal rows | 3 |
| [Ue] rated operational voltage | 240/415 V AC |
| [In] rated current | 100 A |
| [Ui] rated insulation voltage | 500 V |
| Number of ways | 54 ways |
| Cable entry | Knock-out cable entries |
| Type of rail | DIN |
| Enclosure material | Housing: plastic Front face: plastic |
| Width | 486 mm |
| Height | 660 mm |
| Depth | 128 mm |

Environment

| | |
|-------------------------|-------------------------------|
| Standards | AS/NZS 61439-3 AS/NZS 3000 |
| Fire resistance | 650 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK09 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 51.0 cm |
| Package 1 Width | 13.5 cm |
| Package 1 Length | 68.0 cm |
| Package 1 Weight | 5.25 kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 18 |

| | |
|------------------|----------|
| Package 2 Height | 120.0 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 112.8 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|--------|
| Warranty | 7-year |
|----------|--------|