

Product data sheet

Characteristics

RMXPH324

SLIM comb busbar, Clipsal Resi MAX, 3P+N 24 modules 80 A



Main

Product brand	Clipsal
Range	Resi MAX
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P + N
Number of ways	24 ways N + L tooth connector(s) with 9 mm pitch
Distance between way	18 mm
Length in 18 mm modules	24

Complementary

Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N 400 V AC Ph/Ph
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-1
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Bottom on tunnel type terminals
9 mm pitches	48
Width	432 mm
Colour	White (RAL 9003)

Environment

Standards	IEC 61439-1 IEC 60947-7-1
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	8.6 cm
Package 1 Length	46.6 cm
Package 1 Weight	355.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	6 cm
Package 2 Width	8.6 cm
Package 2 Length	46.6 cm

Package 2 Weight	1.778 kg
Unit Type of Package 3	S04
Number of Units in Package 3	30
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	11.296 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations