

# Product datasheet

Specifications

**CLIPSAI**



## A type Residual Current Circuit Breaker, Clipsal Resi MAX, 2P 63A 30mA

RMXRC263

### Main

Range	Resi MAX
Product or component type	Residual current circuit breaker (RCCB)
Product brand	Clipsal
Device application	Protection
Poles description	2P
Number of modules	2
[In] rated current	63 A
network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type A
Rated conditional short-circuit current	6 kA

### Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	240 V
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Surge current	250 A
Size	81 x 36 x 75 mm conforming to DIN 43880
Connection pitch	18 mm
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	73 mm
Product weight	197 g
Embedding depth	44 mm
Colour	White
Mechanical durability	10000 cycles
Electrical durability	4000 cycles
Connections - terminals	Tunnel type terminals - 1...25 mm <sup>2</sup> - flexible Tunnel type terminals - 1...35 mm <sup>2</sup> - rigid

Wire stripping length	14 mm
Tightening torque	3.5 N.m

## Environment

Standards	AS/NZS 61008
Product certifications	RCM CB
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	2
overvoltage category	III
Ambient air temperature for operation	-25...40 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	4 cm
Package 1 Length	9 cm
Package 1 Weight	225 g

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 3

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

EU RoHS Directive Compliant with Exemptions

SCIP Number 2c7837a4-39fc-4abc-96ed-2ef14f8f87c7

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No