

# Product datasheet

Specifications



## Moulded Switchboard Enclosure, MAX9, 63A, 1P, 10kA MCB, Surface Mount, Shallow Base

SAUPW163

### Main

Range	MAX9
Product or component type	Enclosure
Product brand	Clipsal
Poles description	1P
Curve code	C
Device application	Distribution

### Complementary

Provided equipment	Enclosure Miniature circuit breaker (MCB) (1) 1P 63 A 240 V AC Sealing kit Pole filler Padlocking kit
[In] rated current	63 A
[Ue] rated operational voltage	240 V AC 50/60 Hz
Breaking capacity	10 kA at 240 V AC 50/60 Hz
Enclosure material	thermoplastic
Device mounting	Surface
Mounting support	DIN rail
Width	53 mm
Height	133 mm
Depth	95 mm
Total number of 18 mm modules	2
Provision for padlocking	Padlockable
cable entry	Top and bottom Rear entry

### Environment

IP degree of protection	IP30
Ambient air temperature for operation	-25...70 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

---

<b>Package 1 Height</b>	16.2 cm
<b>Package 1 Width</b>	16.4 cm
<b>Package 1 Length</b>	24.8 cm
<b>Package 1 Weight</b>	402.0 g

---


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	<a href="#">REACH Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No