

Product datasheet

Specifications

CLIPSAL



LED downlight, Clipsal - Lighting,
750lm, 3K/4K/6K, white

CLITPDL1C3

Main

Range	Clipsal
Product or component type	Downlight
Device application	Lighting
Market segment	Residential Commercial
Main colour tint	White
Colour tint	White

Complementary

Device mounting	Recessed ceiling
Shape	Round
Type of installation	Indoor/outdoor
Rated power in W	7 W
Light source	LED
Total system power	230 V AC 50 Hz
Luminous flux	750 lm 3000 K warm white 750 lm 4000 K cool white 750 lm 6000 K day light
Colour rendering index	R _a =80
Bulb lifespan	50000 h
Beam angle	90 °
load type	Dimmable LED
Quantity per set	1
Trim width	110 mm
Cut-out dimensions	90 mm
Mounting depth	55 mm
Net weight	0.2 kg

Environment

IP degree of protection	IP44
Insulation contact rating	IC-4
Unified glare rating	< 22
Ambient air temperature for operation	-10...25 °C

Relative humidity	10...95 % non-condensing
-------------------	--------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	9 cm
------------------	------

Package 1 Width	13 cm
-----------------	-------

Package 1 Length	13 cm
------------------	-------

Package 1 Weight	264 g
------------------	-------

Unit Type of Package 2	CAR
------------------------	-----

Number of Units in Package 2	24
------------------------------	----

Package 2 Height	30 cm
------------------	-------

Package 2 Width	27.5 cm
-----------------	---------

Package 2 Length	54 cm
------------------	-------

Package 2 Weight	6.972 kg
------------------	----------

Contractual warranty

Warranty	3-Year
----------	--------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 320

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level 0

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No