

## Product data sheet

### Characteristics

# WS226/2PB-RG

Switch, Weathershield, Push Button, 2-Gang,  
3A, 240VAC, IP66



#### Main

|                           |                                     |
|---------------------------|-------------------------------------|
| Range of product          | Weathershield                       |
| Product or component type | Push-button                         |
| Colour                    | Resistant grey                      |
| Product brand             | Clipsal                             |
| Device presentation       | Basic element with full cover plate |

#### Complementary

|                                |   |
|--------------------------------|---|
| Colour code                    | RG  |
| Actuator                       | Push-button                                       |
| Contacts type and composition  | 1 NO for contacts close<br>1 NC for contacts open |
| Local signalling               | Without light indicator                           |
| Fixing mode                    | By screws   |
| Material                       | Plastic   |
| Marking location               | Marking on surface                                |
| [Ue] rated operational voltage | 440 V AC  |
| Inrush current                 | 10 A  |
| Marking                        | START-STOP  |
| Mounting position              | Horizontal  |

#### Environment

|                         |      |
|-------------------------|------|
| IP degree of protection | IP66 |
|-------------------------|------|

#### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 8.8 cm  |
| Package 1 Width              | 8.8 cm  |
| Package 1 Length             | 8.8 cm  |
| Package 1 Weight             | 223.8 g |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |