

GROUND LIGHTS SPECIFICATION SHEET



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GL040 Ultra low-glare

2W, 215lm ground light

FEATURES

IK rating	IK08
IP rating	IP68
Colour flexibility	Fixed colour
UGR	<10
Walk Over / Drive Over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 70mm
Bathroom zone	1
Efficiency	DRIVER DEPENDANT
Construction Material	Stainless steel (316)
Weight	818g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

A stylish, baffled ground light

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

Can also be powered by a 700mA low voltage driver if more light is needed.

marine-grade stainless steel 316

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
GL040DNBL40	2W	4000K	12°	215	108	2891
GL040DMBL40	2W	4000K	34°	215	108	694
GL040DNBL30	2W	3000K	12°	208	104	2797
GL040DMBL30	2W	3000K	34°	208	104	671
GL040DNBL27	2W	2700K	12°	200	100	2689
GL040DMBL27	2W	2700K	34°	200	100	645

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	3
PLR/350 1-5	N/A	Yes	No	0	1	1
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	3

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/68	Installation tube
GLA01	Square transformer plate

Beam angles: 12° 34°

