






collingwood

01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

one4all Driver Series

one4all design DALI-2, Push-dim, 0-10V

Features

IP rating	IP20
Dimmable Option	Yes (DALI 2, 0-10V, PUSH-DIM)
LED Lifetime	50,000h

Installation information

Insulation Coverable	No
Construction Material	Polycarbonate
Maximum Ambient Temperature	-25°C to +45°C
SELV	Yes
Electric Class (1, 2, 3)	2

Accessories

SOLIS	PS650 compatible with SOLIS panel range	Sold Separately
DOMINO	PS650 compatible with DOMINO panel range	Sold Separately
THEA	PS250 compatible with THEA Downlight range	Sold Separately

PRODUCT CODES

	Finish	Description	Characteristic I
PS6501100MA	White	one4all driver DALI-2, 1-10V, Push-Dim	650-1100mA
PS250600MA	White	one4all driver DALI-2, 1-10V, Push-Dim	250-600mA

Guarantee

5 Years

Features & benefits

DALI Standard IEC 62386-101: 2014, IEC 62386-102: 2014, IEC 62386-207: 2009, DALI-2

ENEC, CE, CB approved by TUV SUD, SAA, Ctick qualified

Adjustable constant current outputs range from 250-1100mA(selectable every 50mA)

Independent ECG and with strain-relief

Built-in with permanent memory for DALI and Push-DIM, 100,000 times memory

Grow wire tested 650° for 30S and 850° for 5S

DALI 1%-100%, Push-DIM, from 100% to 1.5% dimming range

125mm

