



collingwood

5.7W

5.7W



Coastal protected

IP65

IP65 ideal for outdoor areas

## SL220 Mains Voltage

Mains Voltage LED Spike light

### Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	55°C
Weight	SL220AB: TBC, SL220BK: 714g, SL220SS: 1156g, SL220BZ: 694g
Inrush Current	0.07ms 5.2A
Construction Material	Stainless Steel 316
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

### Guarantee

Warranty 7 years

### Features & benefits

- Tiltable for flexible lighting direction to help suit any installation
- SDCM3 ensuring uniform light appearance and consistency
- Single LED and lens combination for maximum efficiency and optimal light distribution
- Choice of material finish to suit different styles

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
SL220SS30MF	Stainless steel	Mains	5.7W	3000K	40°	520	91	

Energy rating is a reflection of the LED light source.


### Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel

### Accessories

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect	Sold Separately

### Beam angle: 40°



Ø62.5mm

440mm

240mm

1156g