

## D25133K-GB

### 26mm SDS-Plus Hammer Drill

The D25133 delivers up to 2 joules of impact energy, Ideal for drilling anchor and fixing holes into concrete and masonry from 4 to 26 mm in diameter. Features 3 drilling modes, hammer drilling for concrete, impact stop for drilling other materials and rotation stop for light chiselling applications. 240V mains powered.

#### Selling Propositions

- Electronic variable speed for total control in any application
- Ideal for drilling anchor and fixing holes into concrete and masonry from 4 to 26 mm in diameter
- Impact-stop for drilling in wood, steel, ceramic and screwdriving applications
- Rotation-stop for light chiselling applications in brick, soft masonry and occasionally concrete
- Mechanical clutch eliminates sudden high-torque reaction should the bit jam
- Didelis smūgiavimo mechanizmas užtikrina didelį našumą ir mažai apkrauna svarbiausius komponentus, todėl įrankis patvaresnis
- Improved sealing for maximum protection from dust ingress ensuring long tool life
- Ergonomic rubber coated back handle design for improved comfort in use
- Rounded ergonomic industrial design allows easy and comfortable handling in any application
- Output air slots designed to protect users' eye
- Guma padengta šoninė rankena padidina naudotojo komfortą

#### Standard Equipment

- Heavy duty carrying case (1)
- Multi position rubber side handle (1)
- Depth stop (1)

#### Warranty specifications

- DEWALT 3 year European PT Guarantee (subject to registration)

Specifications	
Max. Drilling Capacity (Core bit)	50.0 mm
Max. Drilling Capacity (Concrete)	26.0 mm
Max. Drilling Capacity (Metal)	13.0 mm
Max. Drilling Capacity (Wood)	30.0 mm
Impact energy (EPTA 05/2009)	2.6 J
No Load Speed	0-1500 rpm
Hand/Arm Vibration - Hammer drilling into concrete	15.4 m/s <sup>2</sup>
Power Source	Corded
Power Input	800W
Tool Holder	SDS-Plus
Vibration Control	No
Anti Rotation System	No
Clutch	Yes
Dust Solution Compatible	Yes
Perform and Protect	No
Quick Change Chuck	No
Hammer Drilling Mode	Yes
Chipping Mode	Yes
Rotation Only Mode	Yes
Weight	2.6 kg
Height	210.0 mm
Length	335.0 mm
Width	75.0 mm
Uncertainty K 1 (Vibration)	1.5 m/s <sup>2</sup>
Hand/Arm Vibration - Chiselling	14.9 m/s <sup>2</sup>
Uncertainty K 2 (Vibration)	1.5 m/s <sup>2</sup>
Hand/Arm Vibration - Drilling into metal	<2.5
Uncertainty K 3 (Vibration)	1.5 m/s <sup>2</sup>
Hand/Arm Vibration - Screw driving without impact	<2.5
Uncertainty K 4 (Vibration)	1.5 m/s <sup>2</sup>
Sound Pressure	89.0 dB(A)
Sound Pressure Uncertainty	3.0 dB(A)
Sound Power	100.0 dB(A)
Sound Power Uncertainty	3.0 dB(A)
Blows per Minute	0-5500 bpm