

DCS389X2-GB

54V XR FLEXVOLT Reciprocating Saw - 2 X 9Ah

XR FLEXVOLT JUST GOT BETTER. The DCS389 54V Reciprocating Saw has up to 19% more power* when used with a 9Ah battery than the DCS388. With a no-load speed of 3000 spm, this saw delivers the power of a corded reciprocating saw with the portability and convenience of a cordless through our revolutionary DEWALT XR FLEXVOLT technology. With 2 X 9Ah batteries, charger and kitbox. *Products tested under controlled conditions to measure power. Power increase compares peak power of DCS389 with DCB547 and DCS388 with DCB546.

Selling Propositions

- 54v XR FLEXVOLT, Power of the Cord
- DEWALT Brushless Motor for extended run-time, reliability & durability
- Intelligent variable speed trigger and lock off switch
- Two position blade clamp allows for flush cutting and increased versability
- Lever action keyless blade clamp for tool-free blade change
- Pivoting Shoe with open top for high stability and visibility during a cut
- LED for improved visibility of cut
- Ergonomic handle and rubber overmould provide ultimate end user comfort

Standard Equipment

- Multi-voltage XR charger (1)
- DEWALT 18/54 XR FLEXVOLT™ Battery pack 9.0Ah (2)
- T-Stak Kitbox (1)

Warranty specifications

- DEWALT 3 year European PT Guarantee (subject to registration)

Specifications	
No Load Stroke Rate	0 - 3000 spm
Max. Cutting Capacity (Wood)	300.0 mm
Max. Cutting Capacity (Steel Section and Pipes)	130.0 mm
Max. Cutting Capacity [PVC]	160.0 mm
Weight	3.54 kg
Battery Capacity	9.0 Ah
Length	455.0 mm
Height	175.0 mm
Sound Pressure	84.0 dB(A)
Sound Pressure Uncertainty	5.0 dB(A)
Sound Power	95.0 dB(A)
Sound Power Uncertainty	5.0 dB(A)
Hand/Arm Vibration - Cutting boards	15.3 m/s²
Uncertainty K 2 (Vibration)	3.0 m/s²
Hand/Arm Vibration - Cutting wooden beams	15.9 m/s²
Uncertainty K 3 (Vibration)	3.0 m/s²