

DWE4206K-GB

1010W 115mm Angle Grinder

The DWE4206 is a small corded angle grinder powered by a 1010W motor and ideal for workshop or jobsite applications. Dust ejection system removes majority of debris from the air which passes over the motor, preventing abrasion and tracking. With kitbox, 240V mains powered.

Selling Propositions

- Fully leaded stator windings for increased motor durability
- Guard design allows fitment, adjustment or removal without the use of tools, for increased flexibility
- Dust ejection system removes majority of debris from the air which passes over the motor, preventing abrasion and tracking
- Small girth allow comfortable gripping resulting in superior ergonomics
- Side positioned spindle lock gives greater protection to button when using in confined spaces
- Anti lock flange prevents flanges from permanently locking up and locking the disc on
- Anti vibration side handle to improve user comfort
- No-volt release switch prevents the unit from starting unintentionally when locked on. Switch must be consciously reset before power is delivered
- Soft start reduces movement of the tool on startup increasing user control
- Abrasion protected motor for increased durability
- Pop off brushes protect the armature from damage at the end of brush life resulting in greater motor durability
- Brushed motor for optimum performance

Standard Equipment

- Spanner (1)
- Protective keyless guard (1)
- Multi-position anti vibration side handle (1)
- Inner and outer disc flange (1)
- Heavy duty carrying case (1)

Warranty specifications

- DEWALT 3 year European PT Guarantee (subject to registration)

| Specifications | |
|-------------------------------|------------------------|
| Max. Disc Diameter | 115.0 mm |
| No Load Speed | 11000 rpm |
| Variable Speed | No |
| Spindle Thread | M14 |
| Switch type | Slide |
| Power Input | 1010W |
| Power Source | Corded |
| Perform and Protect | No |
| Brake | No |
| Clutch | No |
| Quick Change Flange | Yes |
| Supplied in Kitbox | Yes |
| Weight | 1.85 kg |
| Length | 280.0 mm |
| Height | 80.0 mm |
| Hand/Arm Vibration - Grinding | 8.3 m/s ² |
| Uncertainty K 1 (Vibration) | 2.5 m/s ² |
| Hand/Arm Vibration - Sanding | 1.5 m/s ² |
| Uncertainty K 2 (Vibration) | 1.5 m/s ² |
| Sound Pressure | 89.0 dB(A) |
| Sound Pressure Uncertainty | 3.0 dB(A) |
| Sound Power | 100.0 m/s ² |
| Sound Power Uncertainty | 3.0 dB(A) |