



400A TPN GLASGOW Switch-disconnector (surface-mounted), RAL 7004



Part no. 403GN  
304096

| General specifications                        |  |                                                                                                                          |
|-----------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------|
| Product name                                  |  | Eaton Industrial Switch & Fuse Gear Exel/Glasgow LV systems Switch- & Controlgear Enclosure                              |
| Part no.                                      |  | 403GN                                                                                                                    |
| EAN                                           |  | 9010238196186                                                                                                            |
| Product Length/Depth                          |  | 322 millimetre                                                                                                           |
| Product height                                |  | 521 millimetre                                                                                                           |
| Product width                                 |  | 487 millimetre                                                                                                           |
| Product weight                                |  | 34.07 kilogram                                                                                                           |
| Compliances                                   |  | RoHS conform                                                                                                             |
| Product Tradename                             |  | Industrial Switch & Fuse Gear Exel/Glasgow                                                                               |
| Product Type                                  |  | LV systems                                                                                                               |
| Product Sub Type                              |  | Switch- & Controlgear Enclosure                                                                                          |
| Countries                                     |  | United Arab Emirates<br>United Kingdom of Great Britain and Northern Ireland<br>Central African Republic<br>South Africa |
| Product Specification Details                 |  |                                                                                                                          |
| Construction size (fuse inserts)              |  | Cylindrical                                                                                                              |
| Degree of protection                          |  | Other<br>IP40                                                                                                            |
| Housing depth                                 |  | 322 mm                                                                                                                   |
| Housing height                                |  | 521 mm                                                                                                                   |
| Housing of equipment fuse switch disconnector |  | Other                                                                                                                    |
| Housing width                                 |  | 487 mm                                                                                                                   |
| Number of poles                               |  | Four-pole                                                                                                                |
| Rated insulation voltage (Ui)                 |  | 660 V                                                                                                                    |
| Rated operating voltage (Ue) at AC - max      |  | 415 V                                                                                                                    |
| Rated operational current                     |  | 400 A                                                                                                                    |

Technical data ETIM 9.0

|                                                                                                                                                                                                                      |    |             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-------------|
| Low-voltage industrial components (EG000017) / Fuse switch disconnector with housing (EC000249)                                                                                                                      |    |             |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Safety circuit breaker housing (ec1@ss13-27-37-14-13 [AKF070018]) |    |             |
| Number of poles                                                                                                                                                                                                      |    | 4           |
| Rated operation current Ie                                                                                                                                                                                           | A  | 400         |
| Max. rated operation voltage Ue AC                                                                                                                                                                                   | V  | 415         |
| Rated insulation voltage Ui                                                                                                                                                                                          | V  | 660         |
| Construction size fuse inserts                                                                                                                                                                                       |    | Cylindrical |
| With error protection                                                                                                                                                                                                |    | No          |
| Housing width                                                                                                                                                                                                        | mm | 487         |
| Housing depth                                                                                                                                                                                                        | mm | 322         |
| Height of housing                                                                                                                                                                                                    | mm | 521         |
| Degree of protection (IP)                                                                                                                                                                                            |    | Other       |
| Degree of protection (NEMA)                                                                                                                                                                                          |    | Other       |