


Wall socket



Plug

Ordering details

Voltage	h	Aux. contact	Cable entry	Type	IIB / IIC low temp -55 °C up to +40/+55 °C	IIC high temp -20 °C up to +55 °C	Weight approx.	Order No.
Type 63 A 4-pole								
200-250 V		-	KU	Wall socket		X	8.1 kg	**GHG514 4409 R0001**
		-	ME	Wall socket		X	8.2 kg	**GHG514 4409 R3001**
		-	ME	Wall socket	X		8.2 kg	**GHG514 4409 R3101**
	9			Plug	X	X	0.9 kg	**GHG514 7409 R0001**
380-415 V		-	KU	Wall socket		X	8.1 kg	**GHG514 4406 R0001**
		-	ME	Wall socket		X	8.2 kg	**GHG514 4406 R3001**
		-	ME	Wall socket	X		8.2 kg	**GHG514 4406 R3101**
		-	GM	Wall socket		X	8.2 kg	**GHG514 4406 R3003**
	6	-	GM	Wall socket	X		8.2 kg	**GHG514 4406 R3103**
				Plug	X	X	0.9 kg	**GHG514 7406 R0001**
480-500 V		-	KU	Wall socket		X	8.1 kg	**GHG514 4407 R0001**
		-	ME	Wall socket		X	8.2 kg	**GHG514 4407 R3001**
		-	ME	Wall socket	X		8.2 kg	**GHG514 4407 R3101**
		-	GM	Wall socket		X	8.2 kg	**GHG514 4407 R3003**
	7	-	GM	Wall socket	X		8.2 kg	**GHG514 4407 R3103**
				Plug	X	X	0.9 kg	**GHG514 7407 R0001**
600-690 V		-	KU	Wall socket		X	8.1 kg	**GHG514 4405 R0001**
		-	ME	Wall socket		X	8.2 kg	**GHG514 4405 R3002**
		-	ME	Wall socket	X		8.2 kg	**GHG514 4405 R3102**
	5			Plug	X	X	0.9 kg	**GHG514 7405 R0001**
Type 63 A 5-pole								
200-250 V 380-415 V		-	KU	Wall socket		X	8.1 kg	**GHG514 4506 R0001**
		-	ME	Wall socket		X	8.2 kg	**GHG514 4506 R3001**
		-	ME	Wall socket	X		8.2 kg	**GHG514 4506 R3101**
		-	GM	Wall socket		X	8.2 kg	**GHG514 4506 R3006**
	6	-	GM	Wall socket	X		8.2 kg	**GHG514 4506 R3106**
				Plug	X	X	0.9 kg	**GHG514 7506 R0001**

other voltage ranges and versions, e.g. with aux. contact, on request

KU = 1 x plastic cable glands M40 cable gland, 1 x M40 plastic Ex-screw plug

ME = 2 x metal thread M32 with plastic Ex-screw plug