



Einhell

EXPERT

POWER X-CHANGE

Cordless Sealing Gun

TE-SG 18/10 Li - Solo

Item No.: 4522250

Ident No.: 21011

Bar Code: 4006825661187

The Einhell TE-SG 18/10 Li Solo cordless sealing gun is a member of the flexible PXC family and suitable for 310 ml cartridges. While a slim design and Softgrip provide the basis for a firm hold during operation, the use of robust materials cater for durability even when regularly used. While the maximum dispensing force of this cartridge gun lies at up to 2000 N, its dispensing speed can be adapted by means of an adjusting wheel and a pressure switch to suit the different materials and quantities required from job to job. A reversing mechanism puts an end to material dripping out of the cartridge, a bright LED light provides optimum visibility of the work area. It comes without a battery or charger; these items are available separately.

Features & Benefits

- A member of the Power X-Change family
- High dispensing force of up to 2000 N
- Cordless cartridge gun for 310 ml cartridges
- With bright LED for an optimum view of the work area
- Adjustable speed for various materials and quantities
- Dispensing speed controlled by adjusting wheel + pressure switch
- No dripping due to reversing mechanism
- Robust materials for regular use
- Slimline design with ergonomic Softgrip
- Supplied without a battery or charger (available separately)



Technical Data

- | | |
|---------------------------|---------------|
| - power supply | 18 V |
| - Dispensing force | 2000 N |
| - Feed speed in idle mode | 0.4 - 10 mm/s |
| - Speed settings | 6 settings |
| - Cartridge size max. | 310 mL |

Logistic Data

- | | |
|--------------------------------------|--------------------|
| - Product weight (kg) | 1.8 |
| - Gross weight (kg) | 2.44 |
| - Dimensions single packaging | 435 x 80 x 290 mm |
| - Pieces per export carton | 5 Pieces |
| - Gross weight of export carton | 14.5 kg |
| - Dimensions export carton | 465 x 435 x 305 mm |
| - Container quantity (20"/40"/40"HC) | 2270 4700 5510 |

