



Data Cables – Overall Screened

Application: Internal and external inter-connections of electronic apparatus such as computers, intercoms, signalling and alarm systems.

Conductor: Tinned Annealed Copper Wire

Insulation: Multi-Core – PVC V-75, Multi-Pair – Polypropylene

Paired Cores: Twisted

Screen: Aluminium Tape Screen, Polyester Mylar Tape lapping and Tinned Copper Drain Wire.

Sheath: PVC 4V-75

Voltage: 240V Radial Thickness Sheath – **MUST NOT BE CONNECTED TO MAINS**

Standards: AS1125 (Conductor), AS/NZS 3808 (PVC)

Greenstar: Approved

ELECTRA Part Number	CORES	SIZE	O.D.
EAS7204	4	0.22	4.8
EAS7206	6	0.22	5.7
EAS7208	8	0.22	6.3
EAS7210	10	0.22	7.0
EAS7212	12	0.22	7.4

*O.D. ± 10% = mm *Size = mm²

ELECTRA Part Number	PAIRS	SIZE	O.D.
EAS7201P	1	0.22	4.2
EAS7201PHV*	1	0.22	4.8
EAS7202P	2	0.22	5.7
EAS7203P	3	0.22	5.9
EAS7204P	4	0.22	6.4
EAS7206P	6	0.22	7.5
EAS7208P	8	0.22	8.6
EAS72010P	10	0.22	9.7
EAS72012P	12	0.22	10.3

*(PHV) 0.6/1kV Insulation Radial *O.D. ± 10% = mm *Size = mm

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38